

EZILINE® MORTAR MIX

TECHNICAL DATA

REINSTATEMENT AND REPAIR OF CEMENT MORTAR LINED PIPES AND FITTINGS



EZILINE - PART A

- 20kg bag of premixed mortar
- Eliminates ordering sand and cement separately
- Meets Australian Standard
- Easy storage on site

EZILINE - PART B

- 5 litre container of liquid mix
- Easy to handle and store
- Eliminates decanting from larger drums
- Does not need water added
- A water reducing agent, strengthening agent, and bonding agent, when mixed with Part A
- Less waste

EZILINE USAGE

Pipe OD mm	CML thickness mm	L* mm
660	12	335
813	16	204
960	16	173
1085	16	153
1124	16	147
1219	16	136
1422	19	98
1626	19	86
1829	19	76

*L = length of pipe that could be lined per EZILINE kit

DESCRIPTION

EZILINE Mortar Mix is a high performance product specifically designed for use in reinstating the field joints and repair of Steel Mains cement mortar lined steel pipes and fittings. It is a complete system, including the primer and mortar materials.

When applied as per manufacturer's instructions this product meets the requirements of AS/NZS 4020.

GENERAL APPLICATION

Brush apply a prime coat of Part B [liquid] to cover the steel and adjacent mortar. Do not dilute. Thoroughly manually mix one full bag of Part A [do not use cement mixer] and as much of Part B required to form a stiff workable mixture. Do not add water. Apply the mortar, compacting it into place to the level of the adjacent mortar.

Note: The working time reduces with temperature, and is approximately 20 minutes at 30°C.

TECHNICAL DATA

Part A: The dry mix includes a Type SR blended cement in full compliance with AS 3972 and sand in full compliance with AS 2758.1 classification C.

Part B: The liquid is a high performance acrylic modifier. Certifications: Meets AS/NZS 4020 requirements for water contact.

STEEL MAINS PROPRIETARY LIMITED

125-127 PATULLOS LANE, SOMERTON, VICTORIA 3062 / WWW.STEELMAINS.COM
PHONE +61 (0)3 9217 3110 / EMAIL MARKETING@STEELMAINS.COM

All Steel Mains trademarks and logos are owned by Steel Mains Proprietary Limited. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Steel Mains reserves the right to change specifications without prior notice. SMEZITD0515 © 2015 Steel Mains Proprietary Limited. All Rights Reserved.